WARNING



SECTION 1 : IDENTIFICATION

Product identifier



Trade name : Nitrogen
SDS no : QSE-PD06
Chemical description : Nitrogen
Chemical formula : N2

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses :

- Industrial and professional. Perform risk assessment prior to use.
- Test gas/Calibration gas.
- Purge gas, diluting gas, inerting gas.
- Purging.
- Laboratory use.
- Shield gas for welding processes.
- Use for manufacture of electronic/photovoltaic components.
- Contact supplier for more information on uses.

Details of the supplier of the safety data sheet

Company identification : Société d'oxygène et d'acétylène du Liban S.A.L.
Chekka (North Lebanon), Industrial Area, SOAL Building, Al Sahl Street
Dekwaneh (Mount Lebanon), Industrial Area, SOAL Building , Al Midane Street
customer.care@soal.com.lb
www.soal.com.lb

Emergency telephone number

Emergency telephone number :+961 76 111 900 // +961 26 543 381-7,9 // +961 01 692 380-5

SECTION 2 : HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards:

- Gases under pressure : Compressed gas H280

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified as a dangerous substance / mixture.

Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Prevention : Not Applicable.
- Response : Not Applicable.
- Storage : P410+P403 - Protect from sunlight. Store in a well-ventilated place.

Other hazards: Asphyxiant in high concentrations.

SECTION 3: COMPOSITION/ INFORMATION OR INGREDIENTS

Name	Product Identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	(CAS No) 7727-37-9 (EC no) 231-783-9 (EC index no) ---	100	Not classified	Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

SECTION 4: FIRST AID MEASURES

Description of necessary first aid measures

- Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in a recovery position and get medical attention immediately. Maintain an open airway Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours

- Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion: As this product is a gas, refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Inhalation : At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen.
- Ingestion : As this product is a gas, refer to the inhalation section.
- Skin contact : Contact with rapidly expanding gas may cause burns or frostbite.
- Frostbite : Try to warm up the frozen tissues and seek medical attention
- Eye contact : Contact with rapidly expanding gas may cause burns or frostbite.

Over-exposure signs/symptoms

- Skin contact: No specific data
- Ingestion: No specific data
- Inhalation No specific data
- Eye contact : No specific data

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments : No specific treatment
- Protection of first-aiders :No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media: None known
- Specific hazards arising from the chemical: Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode..
- Hazardous thermal decomposition products: Decomposition products may include the following materials: nitrogen oxides
- Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact the supplier immediately for specialist advice. Move containers from the fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- **Personal precautions :**
  - Try to stop release.
  - Evacuate area.
  - Wear self-contained breathing apparatus when entering an area unless the atmosphere is proved to be safe.
  - Ensure adequate air ventilation.
  - Act in accordance with the local emergency plan.
  - Stay upwind.

- **Environmental Precautions :**
  - Try to stop release

- **Clean up methods :**
  - Ventilate area

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

- **Safe use of the product :**
  - The substance must be handled in accordance with good industrial hygiene and safety procedures.
  - Only experienced and properly instructed persons should handle gases under pressure.
  - Consider pressure relief device(s) in gas installations.
  - Ensure the complete gas system was (or is regularly) checked for leaks before use.
  - Do not smoke while handling products.
  - Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
  - Do not breathe gas.
  - Avoid releasing products into the atmosphere.
- **Safe handling of the gas receptacle** :
  - Refer to supplier's container handling instructions.
  - Do not allow backfeed into the container.
  - Protect cylinders from physical damage; do not drag, roll, slide or drop.
  - When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
  - Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
  - If the user experiences any difficulty operating cylinder valves, discontinue use and contact the supplier.
  - Never attempt to repair or modify container valves or safety relief devices.
  - Damaged valves should be reported immediately to the supplier.
  - Keep container valve outlets clean and free from contaminants particularly oil and water.
  - Replace valve outlet caps or plugs and container caps where supplied as soon as the container is disconnected from equipment.

- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
- Sucking back of water into the container must be prevented.

- **Conditions for safe storage, including any incompatibilities:**
  - Observe all regulations and local requirements regarding storage of containers.
  - Containers should not be stored in conditions likely to encourage corrosion.
  - Container valve guards or caps should be in place.
  - Containers should be stored in the vertical position and properly secured to prevent them from falling over.
  - Stored containers should be periodically checked for general condition and leakage.
  - Keep the container below 50°C in a well ventilated place.
  - Store containers in locations free from fire risk and away from sources of heat and ignition.
  - Keep away from combustible materials.

- **Specific end use(s)** : None.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OEL (Occupational Exposure Limits) : No data available.
DNEL (Derived-No Effect Level) : No data available.
PNEC (Predicted No-Effect Concentration) : No data available.

Exposure controls

- **Appropriate engineering controls:**
  - Provide adequate general and local exhaust ventilation.
  - Systems under pressure should be regularly checked for leakages.
  - Oxygen detectors should be used when asphyxiating gases may be released.
  - Consider a work permit system e.g. for maintenance activities.

- **Individual protection measures, e.g. personal protective equipment**
  - A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
  - PPE compliant to the recommended EN/ISO standards should be selected.

★ Eye/face protection : Wear safety glasses with side shields (Standard EN 166 - Personal eye-protection)

★ Skin protection
- Hand protection : Wear working gloves when handling gas containers (Standard EN 388 - Protective gloves against mechanical risk)

- Other : Wear safety shoes while handling containers (Standard EN ISO 20345 - Personal protective equipment - Safety footwear)

★ Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres (Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask).
★ Thermal hazards : None necessary

- **Environmental exposure controls** : None necessary

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

- Appearance
  - Physical state at 20°C / 101.3kPa : Gas
  - Color : Colorless
- Odor : No odor warning properties
- Odor threshold : Odour threshold is subjective and inadequate to warn of overexposure
- pH value : Not applicable
- Molar mass : 28 g/mol
- Melting point : -210 °C
- Boiling point : -196 °C
- Flash point : Not applicable for gases and gas mixtures
- Critical temperature [°C] : -147 °C
- Evaporation rate (ether=1) : Not applicable for gases and gas mixtures
- Flammability range : Non flammable
- Vapor pressure [20°C] : Not applicable
- Vapor pressure [50°C] : Not applicable
- Relative density, gas (air=1) : 0.97
- Relative density, liquid (water=1) : Not applicable
- Solubility in water : 20 mg/l
- Partition coefficient n-octanol/water [log Kow] : Not applicable for inorganic gases
- Auto-ignition temperature : Not applicable
- Viscosity [20°C] : Not applicable
- Explosive Properties : Not applicable
- Oxidizing Properties : None

Other information

- **Other data** : None.

SECTION 10: STABILITY AND REACTIVITY

- Reactivity: No reactivity hazard other than the effects described in sub-sections below
- Chemical stability: Stable under normal conditions.
- Possibility of hazardous reactions: None.

- Conditions to avoid: None under recommended storage and handling conditions
- Incompatible materials: None

For additional information on compatibility refer to ISO 11114.

- Hazardous decomposition products : None

SECTION 11:TOXICOLOGICAL INFORMATION

Toxicity information : No toxicological effects from this product

SECTION 12:ECOLOGICAL INFORMATION

Ecological effects information : No ecological damage caused by this product

SECTION 13:DISPOSAL CONSIDERATIONS

Disposal Methods: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

SECTION 14:TRANSPORT INFORMATIONS

UN number

UN-No. : 1066

UN proper shipping name

Transport by road/rail (ADR/RID) : NITROGEN, COMPRESSED
Transport by air (ICAO-TI / IATA-DGR) : NITROGEN, COMPRESSED
Transport by sea (IMDG) : NITROGEN, COMPRESSED

Transport hazard class(es)

Labeling:

2: Non-flammable, non-toxic gases

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 1 A
Hazard identification number : 20
Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)
Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)
Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

Packing group
Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

Environmental hazards
Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

Special precautions for user
Packing Instruction(s)

- ❖ Transport by road/rail (ADR/RID) : P200
- ❖ Transport by air (ICAO-TI / IATA-DGR)
- Passenger and Cargo Aircraft : 200
- Cargo Aircraft only : 200
- ❖ Transport by sea (IMDG) : P200
- ❖ Special transport precautions :
- Avoid transport on vehicles where the load space is not separated from the driver's compartment.
- Ensure vehicle drivers are aware of the potential hazards of the load and know what to do in the event of an accident or an emergency.
- Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure the cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure the valve protection device (where provided) is correctly fitted.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.

Seveso directive 96/82/EC : Not covered.

National regulations

National legislation : Ensure all national/local regulations are observed.

Water hazard class (WGK) : -

Kenn-Nr. : 1351

Chemical safety assessment : A CSA does not need to be carried out for this product.

SECTION 16: OTHER INFORMATION

NFPA Nitrogen



